

ORSL Log

PLEASE NOTE THAT ALL RULES AND POLICIES THAT ARE IN EFFECT AT THE DATE OF THE ISSUANCE OF THIS NOTIFICATION ARE SUBJECT TO CHANGE. PLEASE CONTACT SAFETY/RULES TO DETERMINE VALIDITY BEFORE YOU USE THE INFORMATION IN THIS MESSAGE.

Open Date	Ticket	Sub	Question	Answer	Rule Book	Rule No
7/19/2021						
	15843	BIGHOR	May a bulk head flat car loaded with railroad wheels be placed next to a loaded tank car found in Group B?	Yes. Loaded tank car from Group B must not be next to loaded flat cars, except closed TOFC/COFC equipment, multi-levels, and other specially equipped cars with tie down devices for handling vehicles. Railroad wheels loaded on wheel car flats, in gondolas with no ends, or loaded with the axles above the top of the car.	USHMI	VI(6)
7/22/2021						
	15846	CHILLI	Does the 3,000 trailing tons include one of the cars in a long car/short car train makeup restriction?	No. The long car/short car combo cannot have more than 3,000 trailing tons behind them. It does not include either of the 2 cars.	SSI	Item 47
7/24/2021						
	15848	NEEDLE	What type of air test must be performed after switching a portion of pre-tested cars for train makeup and/or hazardous material car placement compliance?	Perform a Class 1 Air Brake Test on the portion of train that was rearranged for train makeup and/or hazardous material car placement compliance. A Class 3 Air Brake Test must be performed on the cars that remained consecutively coupled and were pre-tested.	ABTH	100.10
	15849	GALLUP	May a loaded open top coil car be placed next to a loaded tank car?	Yes.	GCOR	1.37
	15850	BARSTO	May a vehicle car with handbrakes applied be left in the skates as the only car in the track at Barstow Hump Yard?	Yes, per GN 391(13)3: When pulling cars out of the bowl, leave at least one car in the track with east wheels in the west end of skate retarders with handbrake applied. When adding cars to a bowl track from east end, leave east wheels in east end of skate retarders.	G/N	391
	15851	EMPORI	What is the maximum train length allowed, excluding locomotives, for a solid loaded conventional vehicle train operating as an "H" symbol?	Loaded vehicle trains cannot exceed 8,000 feet between lead locomotive consist and ETD on rear.	SSI	Item 47(A)2