

ORSL Log

PLEASE NOTE THAT ALL RULES AND POLICIES THAT ARE IN EFFECT AT THE DATE OF THE ISSUANCE OF THIS NOTIFICATION ARE SUBJECT TO CHANGE. PLEASE CONTACT SAFETY/RULES TO DETERMINE VALIDITY BEFORE YOU USE THE INFORMATION IN THIS MESSAGE.

Open Date	Ticket	Sub	Question	Answer	Rule Book	Rule No
11/8/2021						
	16192	CLOVIS	Must the mid DP LXA unit be linked to the lead locomotive to utilize ETD repeater?	Yes. Mid DP Remote must be LXA equipped and must be linked to lead locomotive of train.	OTHER	QRC
	16194	HASTIN	May a railroad-supplied electronic device (iPad) be used as a train list while on the ground switching cars?	No.	GCOR	2.21
	16196	GLASGO	May a crew member request "going between" protection by radio while in the cab of the lead locomotive when coupled to rail equipment?	Yes. The engineer must respond by radio "set and centered".	TYESR	13.1.1
11/9/2021						
	16197	GALLUP	What is the placement instruction for a single DP remote consist cut into a manifest train?	A single DP remote consist cut into the train must not have the cut in DP consist further than 10,000 feet from the head end of train (excluding locomotive length). Single DP consists cut into the train exceeding 8 RPA must be cut in at 300 tons per axle exceeding 8 RPA, but no closer to the head end than 20 cars forward of mid-train, by car count, as long as train makeup requirements next to DP remote consist outlined in Item 47(A) 3 and 4 are met.	SSI	Item 47(2)a
11/11/2021						
	16200	SPOKAN	May an engineer provide his own "going between" protection to release or apply hand brakes on cars in the train?	No. The locomotive(s) must not be left "unattended" as defined in ABTH glossary.	TYESR ABTH	13.1.1 Glossary
11/12/2021						
	16206	PANHAN	Must the lead DP consist and the cut in remote consist both be equipped with LXA to operate trains greater than 10,000 feet with an ETD?	No. Only the cut in remote consist is required to be equipped with LXA when operating trains greater than 10,000 feet with an ETD.	SSI	Item 47
11/13/2021						
	16207	KOOTEN	Must the mid DP LXA unit be linked to the lead locomotive to utilize ETD repeater?	Yes. Mid DP Remote must be LXA equipped and must be linked to lead locomotive of train.	OTHER	QRC

Open Date	Ticket	Sub	Question	Answer	Rule Book	Rule No
	16208	STJOSE	May equipment be left ahead of the clearance marker in a yard track?	No. Do not leave equipment standing where it will foul equipment on adjacent tracks or cause injury to employees riding on the side of a car or engine. On tracks where clearance point is indicated, leave equipment beyond the clearance point.	GCOR	7.1
	16213	GALLUP	Does the long car/short car restriction also apply to a short car/long car scenario?	Yes.	SSI	Item 47